



DS-7300HWI-SH Series DVR
Technical Specification

Notices

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2013 by HIKVISION. All rights reserved.

This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied. It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

This documentation is provided “as-is,” without warranty of any kind.

Please send any comments regarding the documentation to:

overseasbusiness@hikvision.com

Find out more about HIKVISION at www.hikvision.com

Main Features

- **Main stream supports encoding at up to WD1 resolution in real time and sub stream at CIF/QCIF resolution in real time.**
- **Simultaneous HDMI, VGA and CVBS outputs.**
- **HDMI output and VGA output at up to 1920×1080P resolution.**
- **Channel-zero encoding.**
- **Support dual stream.**
- **HDD quota management; different capacity can be assigned to different channel.**
- **Holiday recording schedule configuration.**
- **Smart searching for the event triggered record files.**
- **Digital zoom of video in live view or playback mode.**
- **Up to 4/8/16-ch synchronous playback.**
- **1 self-adaptive 10M/100M/1000M network interface.**
- **IPv6 is supported.**
- **Network detection function.**
- **NTP, SMTP, NFS, UPnP™ and iSCSI protocols supported.**

Functions & Performances

General

- PAL/NTSC adaptive video inputs.
- H.264 video compression with high reliability and superior definition.
- Each channel supports dual-stream.
- Main stream supports encoding at up to WD1 (PAL: 960×576, NTSC: 960×480) resolution in real time and sub stream at CIF/QCIF resolution.
- Independent configuration for each channel, including resolution, frame rate, bit rate, image quality, etc.
- The quality of the input and output video is configurable.
- Normal and event recording parameters configurable for per individual camera.
- Encoding for both audio/video composite stream and video stream; audio and video synchronization during composite stream encoding.
- Watermark technology.

Local Monitoring

- Simultaneous HDMI, VGA and CVBS outputs.
- HDMI/VGA output at up to 1920×1080P resolution.
- 1/4/6/8/9/16/25/36-division live view is supported, and the display sequence of screens is adjustable.
- Live view screen can be switched in group, and manual switch and automatic cycle review is also provided, the interval of automatic cycle can be adjusted.
- Quick setting menu is provided for live view.
- The selected live view channel can be shielded.
- Motion detection, tamper-proof, video exception and video loss alarm functions.
- Privacy mask.
- Several PTZ protocols supported; PTZ preset, patrol and pattern.
- Zooming in by clicking the mouse and PTZ tracing by dragging mouse.

HDD Management

- 4 SATA hard disks can be connected, with a maximum of 4TB storage capacity for each disk.
- 8 network disks (8 NAS disks, or 7 NAS disks+1 IP SAN disk) can be connected.
- 1 eSATA hard disk interface.
- HDD group management.
- Support HDD standby function.
- HDD property: redundancy, read-only, read/write (R/W).
- HDD quota management; different capacity can be assigned to different channel.

Recording and Playback

- Holiday recording schedule configuration.
- Normal and event video encoding parameters.
- Multiple recording types: manual, normal, motion, alarm, motion/alarm and motion & alarm.
- 8 recording time periods with separated recording types.
- Pre-record and post-record for motion detection for recording, and pre-record time for schedule and manual recording.
- Searching record files by event.
- Customization of tags, searching and playing back by tags.
- Locking and unlocking record files.
- Local redundant recording.
- Searching and playing back record files by channel number, recording type, start time, end time, etc.
- Smart search for the selected area in the video.
- Zooming in when playback.
- Playing reversely.
- Supports pause, speed up, speed down, skip forward, and skip backward when playback, locating by dragging the mouse.
- Up to 4/8/16-ch synchronous playback.

Backup

- Export video data by USB, SATA or eSATA storage device.
- Export video clips when playback.
- Management and maintenance of backup devices.

Alarm and Exception

- Configurable arming time of alarm input/output.
- Alarm for video loss, motion detection, tampering, abnormal signal, video input/output standard mismatch, illegal login, network disconnected, IP conflict, abnormal record, HDD error, and HDD full, etc.
- Alarm event triggers full screen monitoring, audio alarm, notifying surveillance center and sending email.
- Automatic restore when system is abnormal.

Other Local Functions

- Operable by mouse, or IR remote control.
- Three-level user management; admin user is allowed to create many operating accounts and define their operating permission, which includes the limit to access any channel.
- Operation, exceptions and log recording and searching.
- Import and export of device configuration information.

Network Functions

- 1 self-adaptive 10M/100M/1000M network interface.

- IPv6 is supported.
- TCP/IP protocol, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, UPnP™, NFS, and iSCSI are supported.
- TCP, UDP and RTP for unicast.
- Remote search, playback, download, locking and unlocking the record files, and downloading files broken transfer resume.
- Remote parameters setup; remote import/export of device parameters.
- Remote viewing of the device status, system logs and alarm status.
- Remote locking and unlocking of control panel and mouse.
- Remote HDD formatting and program upgrading.
- Remote system restart.
- RS-232 and RS-485 transparent channel transmission.
- Alarm event and exception information can be sent to the remote host.
- Remotely start/stop recording.
- Upgrade by remote FTP server.
- Remote PTZ control.
- Two-way audio and voice broadcasting.
- Embedded WEB server.

Development Scalability:

- SDK for Windows and Linux system.
- Source code of application software for demo.
- Development support and training for application system.

Panels & Interfaces

Front Panel


DS-7300HWI-SH:




- ① Power Button
- ② IR Receiver
- ③ USB Interface
- ④ DVD-ROM
- ⑤ Status Indicator(Power, Ready, Status, Alarm, HDD, Tx/Rx)
- ⑥ Compound Buttons
- ⑦ DIRECTION/ENTER Buttons
- ⑧ JOG SHUTTLE Control

Rear Panel


DS-7304HWI-SH:



DS-7308HWI-SH:




DS-7316HWI-SH:



- ① VIDEO IN
- ② MAIN VIDEO OUT, SPOT VIDEO OUT
- ③ HDMI Interface
- ④ USB Interface
- ⑤ RS-232 Serial Interface
- ⑥ VGA Interface
- ⑦ AUDIO IN, RCA Connector
- ⑧ AUDIO OUT, RCA Connector
- ⑨ LAN Network Interface
- ⑩ RS-485 Serial Interface
- ⑪ ALARM IN/OUT
- ⑫ eSATA Interface
- ⑬ 110~240VAC Power Input
- ⑭ Power Switch
- ⑮ GND

DS-732HWI-SH:



Note: DS-7324HWI-SH model provides 24 video input interfaces on the rear panel.

- ① MAIN VIDEO OUT, SPOT VIDEO OUT
- ② VIDEO IN
- ③ AUDIO OUT(CVBS/VGA), RCA Connector
- ④ LINE IN
- ⑤ AUDIO IN, RCA Connector
- ⑥ VGA Interface
- ⑦ HDMI Interface
- ⑧ USB Interface
- ⑨ LAN Network Interface
- ⑩ RS-232 Interface
- ⑪ Termination Switch
- ⑫ RS-485, Keyboard Serial Interface
- ⑬ ALARM IN, ALARM OUT
- ⑭ eSATA Interface
- ⑮ GND
- ⑯ 110~240VAC Power Input
- ⑰ Power Switch

Specifications

Model		DS-7304 HWI-SH	DS-7308 HWI-SH	DS-7316 HWI-SH	DS-7324 HWI-SH	DS-7332 HWI-SH
Video/Audio input	Video compression	H.264				
	Video input	4-ch	8-ch	16-ch	24-ch	32-ch
	Video input interface	BNC (1.0 Vp-p, 75 Ω), PAL /NTSC self-adaptive				
	Audio compression	G.711u				
	Audio input	4-ch, RCA (2.0 Vp-p, 1 kΩ)				
	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)				
Video/Audio output	HDMI/VGA output	1-ch, resolution: 1080P: 1920×1080/60Hz, SXGA: 1280×1024/60Hz, 720P: 1280×720/60Hz, XGA: 1024×768/60Hz				
	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480				
	Video spot out	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480				
	Encoding resolution	WD1 / 4CIF / 2CIF / CIF / QCIF				
	Frame rate	25 fps (P) / 30 fps (N)				
	Video bit rate	32 Kbps ~ 3072 Kbps, or user defined (Max. 3072 Kbps)				
	Audio output	2-ch, RCA (Linear, 600 Ω)				
	Audio bit rate	64 Kbps				
	Dual-stream	Support; Sub-stream: CIF / QCIF @ 25 fps (P) / 30 fps (N)				
	Stream type	Video, Video & Audio	Channel1-4: Video, Video & Audio; Other channels: Video			
	Synchronous playback	4-ch	8-ch	16-ch		
Hard disk	SATA	4 SATA interfaces				
	eSATA	1 eSATA interface				
	Capacity	Up to 4TB capacity for each disk				
External interface	Network interface	1, RJ45 10M / 100M / 1000M Ethernet interface				
	Serial interface	1 RS-232, RS-485(half-duplex), Keyboard			1 RS-232, RS-485(full-duplex), Keyboard	
	USB interface	3 × USB 2.0				
	Alarm in	4	8	16	16	
	Alarm out	1	4	4	8	
General	Power supply	100~240VAC, 5A, 50~60Hz				
	Consumption (without HDD or DVD-R/W)	≤ 25 W	≤ 30 W	≤ 35 W	≤ 40 W	
	Working temperature	-10 °C ~+55 °C				
	Working humidity	10% ~ 90%				
	Chassis	19-inch rack-mounted 1.5U chassis				
	Dimensions (W × D × H)	445 × 390 × 70 mm				
	Weight (without HDD or DVD-R/W)	≤ 5 kg				